



40170 Bonding Putty

PRODUCT INFORMATION:

40170 is a fiberglass reinforced, non-flowing, pumpable, polyester adhesive with improved flow, spread, and hang characteristics. 40170 should be used where a bonding putty is required. It can also be used to radius, fill or for fairing. 40170 excels in its adhesion qualities, fiberglass to fiberglass. 40170 flows very easily, but displays excellent vertical hang properties. 40170 also spreads and feathers smoothly. 40170 does not require flammable labels or segregation in storage as a flammable, because it has been independently tested to be a non-flammable solid.

GENERAL PROPERTIES:

Viscosity:	Stable non-flowing paste
Catalyst:	MEK Peroxide
Shelf Life:	6 months (stored out of sun)
Pot Life	20 to 30 minutes with 1% DDM-9 at 76 deg. F
Wt/Gallon:	11 pounds
Chemically:	Polyester resin and fillers

USES FOR 40170:

- Power craft
- Sailboats
- Yachts
- Mobile homes
- Travel trailers
- Truck cab
- Automotive
- Most other fiberglass applications

Notice: This information is presented in good faith, but no warranty expressed or implied is given. The information, to our best knowledge, is true and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control.

Revised April 2015