



# 60236-DP Light Weight Deck and Hull Bonding Putty

## PRODUCT INFORMATION:

60236-DP is a pumpable, light weight, non-flowing paste. 60236-DP is designed to be 6 to 6.5 pounds/gallon which will reduce weight in the boat compared to heavier weight putties. 60236-DP can be used to fill larger cavities because of low exotherm and shrink qualities.

## GENERAL PROPERTIES:

Viscosity:	Stable non-flowing paste
Catalyst:	MEK Peroxide
Shelf Life:	6 months (stored out of sun)
Pot Life:	45 to 55 minutes with 1% DDM-9 at 76 deg. F
Pot Life	18 to 25 minutes with 2% of 50% BPO Paste 76 deg. F.
Weight/Gallon	6 to 6.5 lbs.
Chemically:	Polyester resin and fillers
Flash Point:	Closed cup 89 deg. to 90 deg. F.

## USES FOR 60236-DP:

- Power craft
- Sailboats
- Yachts
- Mobile homes
- Travel trailers
- Truck cab
- Automotive
- Most other fiberglass applications

Notice: This information is presented in good faith, but no warranty expressed or implied is given. The information, to our best knowledge, is true and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control.

Revised April 2015