



60239-10 Bonding Putty

PRODUCT INFORMATION:

60239-10 is a non-flowing, pumpable, polyesters adhesive with improved flow, spread, and hang characteristics. 60239-10 should be used where a bonding putty is required. It can also be used to radius, fill or for fairing. 60239-10 excels in its adhesion qualities, fiberglass to fiberglass. 60239-10 flows very easily, which means lower air pressures can be used at the pump, and MEKP mixes in with ease, and yet, 60239-10 displays excellent vertical hang properties. 60239-10 also spreads and feathers smoothly. 60239-10 does not require flammable labels or segregation in storage as a flammable, because it has been independently tested to be a non-flammable solid. Gel times can be varied for specific needs.

GENERAL PROPERTIES:

Viscosity:	Stable non-flowing paste
Catalyst:	MEK Peroxide
Shelf Life:	6 months (stored out of sun)
Pot Life	10 to 15 minutes with 1% DDM-9 at 76 deg. F
Sp. Gr.:	1.06 to 1.078
Wt/Gallon:	9 pounds
Chemically:	Polyester resin and fillers

USES FOR 60239-50:

- Power craft
- Sailboats
- Yachts
- Mobile homes
- Travel trailers
- Truck cab
- Automotive
- Most other fiberglass applications

Caution: Use with adequate ventilation. Keep away from heat, sparks or open flames. If taken internally, induce vomiting and consult a physician.

Notice: This information is presented in good faith, but no warranty expressed or implied is given. The information, to our best knowledge, is true and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control.

Revised April 2015