



72225 High Strength Bonding Putty

PRODUCT INFORMATION:

72225 is a isophthalic, fiberglass reinforced, polyester adhesive. 72225 should be used where a bonding putty is required. It can also be used to radius, fill or for fairing. 72225 also spreads and feathers smoothly.

GENERAL PROPERTIES:

Viscosity:	Stable non-flowing paste
Catalyst:	MEK Peroxide
Shelf Life:	6 months (stored out of sun)
Pot Life	25 to 30 minutes with 1.5% DDM-9 at 76 deg. F
Weight/Gallon	10 lb.
Chemically:	Polyester resin and fillers
Flash Point:	Closed cup 89 deg. to 90 deg. F.

USES FOR 72225

- Power craft
- Sailboats
- Yachts
- Mobile homes
- Travel trailers
- Truck cab
- Automotive
- Most other fiberglass applications

Notice: This information is presented in good faith, but no warranty expressed or implied is given. The information, to our best knowledge, is true and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control.

Revised: April 2015

DBF, Inc. 18576 Krause PO Box 2385 Riverview, MI 48193
Phone: 734-285-1480 Fax: 734-285-1481 Website: dbf-inc.com Email: custserv@dbf-inc.com