



## 72505 High Strength Polyester Adhesive

### PRODUCT INFORMATION:

72505 is a fiberglass reinforced, isophthalic polyester adhesive with high chemical and heat resistance. 72505 should be used where a bonding putty is required. It can also be used to radius, fill or fairing. 72505 displays excellent vertical hang properties. 72505 also spreads and feathers smoothly.

### GENERAL PROPERTIES:

Viscosity:	Stable non-flowing paste
Catalyst:	MEK Peroxide
Shelf Life:	3 months (stored out of sun)
Pot Life	3 to 5 minutes with 1% MEKP at 76 deg. F
Sp. Gr.:	1.33-1.35
Wt/Gallon:	11.25 pounds
Chemically:	Polyester resin and fillers
Flash Point:	Closed cup 89 deg. to 90 deg. F.

### USES FOR 72505:

- Power craft
- Sailboats
- Yachts
- Mobile homes
- Travel trailers
- Truck cab
- Automotive
- Most other fiberglass applications

Notice: This information is presented in good faith, but no warranty expressed or implied is given. The information, to our best knowledge, is true and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control.

Revised: April 2015

DBF, Inc. 18576 Krause PO Box 2385 Riverview, MI 48193  
Phone: 734-285-1480 Fax: 734-285-1481 Website: [dbf-inc.com](http://dbf-inc.com) Email: [custserv@dbf-inc.com](mailto:custserv@dbf-inc.com)