



72625 Fillet Putty

PRODUCT INFORMATION:

72625 is a fiberglass reinforced, isophthalic polyester adhesive with high chemical and heat resistance. 72625 should be used where a bonding putty is required. It can also be used to radius, fill or fairing. 72625 displays excellent vertical hang properties. 72625 also spreads and feathers smoothly.

GENERAL PROPERTIES:

Viscosity:	Stable non-flowing paste
Catalyst:	MEK Peroxide
Shelf Life:	6 months (stored out of sun)
Pot Life	20 to 25 minutes with 1.5% MEKP at 76 deg. F
Sp. Gr.:	1.33-1.35
Wt/Gallon:	11.25 pounds
Chemically:	Polyester resin and fillers
Flash Point:	Closed cup 89 deg. to 90 deg. F.

USES FOR 72625:

Power craft
Sailboats
Yachts
Mobile homes
Travel trailers
Truck cab
Automotive
Most other fiberglass applications

Caution: Use with adequate ventilation. Keep away from heat, sparks or open flames. If taken internally, induce vomiting and consult a physician.

Notice: This information is presented in good faith, but no warranty expressed or implied is given. The information, to our best knowledge, is true and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control.

Revised: April 2015