



60138 Brushable Bonding Putty

PRODUCT INFORMATION:

60138 Brushable is a low viscosity, flowable adhesive. 60138 Brushable can be used for bonding, fairing, filling, radius, and bedding applications.

GENERAL PROPERTIES:

Viscosity: Stable non-flowing paste
Catalyst: MEK Peroxide
Shelf Life: 6 months (stored out of sun)
Standard Pot Life: 22 to 30 minutes with 2% DDM-9 at 76 deg. F.

Sp. Gr.: 0.98 to 1.02
Wt/Gallon: 8 to 8.5 pounds
Chemically: Polyester resin and fillers
Flash Point: Closed cup 89 deg. to 90 deg. F.

USES FOR 60138 Brushable:

Power craft
Sailboats
Yachts
Mobile homes
Travel trailers
Truck cab
Automotive
Most other fiberglass applications

Notice: This information is presented in good faith, but no warranty expressed or implied is given. The information, to our best knowledge, is true and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control.

Revised August 2019

DBF, Inc. 18576 Krause PO Box 2385 Riverview, MI 48193
Phone: 734-285-1480 Fax: 734-285-1481 Website: dbf-inc.com Email: custserv@dbf-inc.com